

Graphical symbols
Safety colours and safety signs
Registered safety signs

La norma prescrive i segnali di sicurezza da utilizzare nella prevenzione degli infortuni, nella protezione dal fuoco, per l'informazione sui pericoli alla salute e nelle evacuazioni di emergenza.

La forma e il colore di ogni segnale di sicurezza sono conformi alla ISO 3864-1 e la progettazione dei segni grafici è conforme alla ISO 3864-3.

La norma è applicabile a tutti i siti in cui le questioni legate alla sicurezza delle persone necessitano di essere poste. Comunque, non è applicabile ai segnali utilizzati nel traffico ferroviario, stradale, fluviale, marittimo e aereo e, in generale, in quei settori soggetti a una regolamentazione che può differire in alcuni punti della presente norma e della serie ISO 3864.

La norma specifica gli originali dei segnali di sicurezza che possono essere ridotti o ingranditi per esigenze di riproduzione e di applicazione.

TESTO INGLESE

La presente norma è la versione ufficiale in lingua inglese della norma europea EN ISO 7010 (edizione luglio 2012).

La presente norma sostituisce la UNI 7544-1:1976, UNI 7544-2:1985, UNI 7544-3:2008, UNI 7544-4:1985, UNI 7544-5:1985, UNI 7544-7:1986, UNI 7544-12:1994, UNI 7544-13:1995, UNI 7544-14:2008, UNI 7544-16:2007, UNI 7545-1:1976, UNI 7545-2:1976, UNI 7545-3:1976, UNI 7545-4:1976, UNI 7545-5:1976, UNI 7545-7:1976, UNI 7545-8:1976, UNI 7545-9:1985, UNI 7545-10:1976, UNI 7545-12:1978, UNI 7545-19:1986, UNI 7545-20:1989, UNI 7545-23:1994, UNI 7545-24:1994, UNI 7545-25:1994, UNI 7545-26:1994, UNI 7545-27:1994, UNI 7545-28:1994, UNI 7545-30:2007, UNI 7546-1:1976, UNI 7546-3:2008, UNI 7546-4:2008, UNI 7546-6:1978, UNI 7546-7:2009, UNI 7546-10:1994, UNI 7546-11:1994, UNI 7546-12:1994, UNI 7546-13:1994, UNI 7546-16:2007, UNI 7546-17:2007, UNI 7546-18:2007, UNI 7547-1:1976, UNI 7547-2:1976, UNI 7547-3:1976, UNI 7547-4:1976, UNI 7547-5:1976, UNI 7547-6:1976, UNI 7547-7:1994, UNI 7547-8:1987, UNI 7547-9:1994, UNI 7547-10:1994, UNI 7547-11:1995.

ICS 01.080.10; 01.080.20

PREMESSA NAZIONALE

La presente norma costituisce il recepimento, in lingua inglese, della norma europea EN ISO 7010 (edizione luglio 2012), che assume così lo status di norma nazionale italiana.

La presente norma è stata elaborata sotto la competenza delle Commissioni Tecniche UNI

Disegni tecnici e documentazione tecnica di prodotto

Sicurezza

Alla data di pubblicazione della presente norma è in vigore il Titolo V "Segnaletica di salute e sicurezza sul lavoro" del Decreto Legislativo 9 aprile 2008, n. 81 "Attuazione dell'articolo 1 della legge 3 agosto 2007, n. 123, in materia di tutela della salute e della sicurezza nei luoghi di lavoro" e successive modifiche e/o integrazioni.

La presente norma è stata ratificata dal Presidente dell'UNI ed è entrata a far parte del corpo normativo nazionale il 18 ottobre 2012.

Le norme UNI sono elaborate cercando di tenere conto dei punti di vista di tutte le parti interessate e di conciliare ogni aspetto conflittuale, per rappresentare il reale stato dell'arte della materia ed il necessario grado di consenso.

Chiunque ritenesse, a seguito dell'applicazione di questa norma, di poter fornire suggerimenti per un suo miglioramento o per un suo adeguamento ad uno stato dell'arte in evoluzione è pregato di inviare i propri contributi all'UNI, Ente Nazionale Italiano di Unificazione, che li terrà in considerazione per l'eventuale revisione della norma stessa.

Le norme UNI sono revisionate, quando necessario, con la pubblicazione di nuove edizioni o di aggiornamenti.

È importante pertanto che gli utilizzatori delle stesse si accertino di essere in possesso dell'ultima edizione e degli eventuali aggiornamenti.

Si invitano inoltre gli utilizzatori a verificare l'esistenza di norme UNI corrispondenti alle norme EN o ISO ove citate nei riferimenti normativi.

ICS 01.080.20; 01.080.10

English Version

Graphical symbols - Safety colours and safety signs -
Registered safety signs (ISO 7010:2011)

Symboles graphiques - Couleurs de sécurité et signaux de
sécurité - Signaux de sécurité enregistrés (ISO 7010:2011)

Graphische Symbole - Sicherheitsfarben und
Sicherheitszeichen - Registrierte Sicherheitszeichen (ISO
7010:2011)

This European Standard was approved by CEN on 23 June 2012.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents	Page
Foreword.....	3

Foreword

The text of ISO 7010:2011 has been prepared by Technical Committee ISO/TC 145 “Graphical symbols” of the International Organization for Standardization (ISO) and has been taken over as EN ISO 7010:2012.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2013, and conflicting national standards shall be withdrawn at the latest by January 2013.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Endorsement notice

The text of ISO 7010:2011 has been approved by CEN as a EN ISO 7010:2012 without any modification.

**Graphical symbols — Safety colours and
safety signs — Registered safety signs**

*Symboles graphiques — Couleurs de sécurité et signaux de sécurité —
Signaux de sécurité enregistrés*



Reference number
ISO 7010:2011(E)

© ISO 2011



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	Referents and categorization of safety signs	2
4.1	General	2
4.2	Referent (safety meaning)	3
4.3	Categorization of safety signs	6
5	Registered safety signs	6
Bibliography		124

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 7010 was prepared by Technical Committee ISO/TC 145, *Graphical symbols*, Subcommittee SC 2, *Safety identification, signs, shapes, symbols and colours*.

This second edition cancels and replaces the first edition (ISO 7010:2003), as well as ISO 6309:1987. It also incorporates the Amendments

ISO 7010:2003/Amd. 1:2006,

ISO 7010:2003/Amd. 2:2007,

ISO 7010:2003/Amd. 3:2007,

ISO 7010:2003/Amd. 4:2009,

ISO 7010:2003/Amd. 5:2010,

ISO 7010:2003/Amd. 6:2010,

ISO 7010:2003/Amd. 7:2010, and

ISO 7010:2003/Amd. 8:2011.

Introduction

There is a need to standardize a system of giving safety information that relies as little as possible on the use of words to achieve understanding.

Continued growth in international trade, travel and mobility of labour requires a common method of communicating safety information.

Lack of standardization may lead to confusion and the risk of accidents.

The use of standardized safety signs does not replace proper work methods, instructions and accident prevention training or measures. Education is an essential part of any system that provides safety information.

The safety signs are intended for use only where there is a risk to people. They may appear in safety signage in workplaces and public areas, safety manuals and notices, product labelling and escape and evacuation plans, as appropriate.

This International Standard is intended to be used by all Technical Committees within ISO charged with developing specific safety signing for their industry, to ensure that there is only one safety sign for each safety meaning. It is also intended that this International Standard be revised regularly to include safety signs as they are standardized by ISO, and which conform to the design principles given in ISO 3864.

The safety signs in this International Standard have been validated by ISO/TC 145/SC 2 according to procedures of standardization current at the time of publication.

NOTE 1 Some countries' statutory regulations may differ in some respects from those given in this International Standard.

NOTE 2 Information on procedures, criteria of acceptability, safety sign templates and application of safety signs are given on the website: <http://www.iso.org/tc145/sc2>.

Graphical symbols — Safety colours and safety signs — Registered safety signs

IMPORTANT — The colours represented in the electronic file of this International Standard can be neither viewed on screen nor printed as true representations. Although the copies of this International Standard printed by ISO have been produced to correspond (with an acceptable tolerance as judged by the naked eye) to the requirements of ISO 3864-4, it is not intended that these printed copies be used for colour matching. Instead consult ISO 3864-4 which provides colorimetric and photometric properties together with, as a guideline, references from colour order systems.

1 Scope

This International Standard prescribes safety signs for the purposes of accident prevention, fire protection, health hazard information and emergency evacuation.

The shape and colour of each safety sign are according to ISO 3864-1 and the design of the graphical symbols is according to ISO 3864-3.

This International Standard is applicable to all locations where safety issues related to people need to be addressed. However, it is not applicable to the signalling used for guiding rail, road, river, maritime and air traffic and, in general, to those sectors subject to a regulation which may differ with regard to certain points of this International Standard and of the ISO 3864 series.

This International Standard specifies the safety sign originals that may be scaled for reproduction and application purposes.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3864-1 *Graphical symbols — Safety colours and safety signs — Part 1: Design principles for safety signs and safety markings*

ISO 3864-3, *Graphical symbols — Safety colours and safety signs — Part 3: Design principles for graphical symbols for use in safety signs*

ISO 3864-4, *Graphical symbols — Safety colours and safety signs — Part 4: Colorimetric and photometric properties of safety sign materials*

ISO 17724, *Graphical symbols — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 17724 and the following apply.

3.1

image content

written description of the elements of a graphical symbol or safety sign and their relative disposition

3.2

referent

idea or object that a graphical symbol is intended to represent

3.3

safety sign

sign giving a general safety message, obtained by a combination of a colour and geometric shape and which, by the addition of a graphical symbol, gives a particular safety message

3.4

safety sign original

safety sign with which a referent, a graphical representation and a description of the application are associated

3.5

supplementary sign

sign that is supportive of another sign and the main purpose of which is to provide additional clarification

4 Referents and categorization of safety signs

4.1 General

The summaries in 4.2 and 4.3 are provided to facilitate the search for registered safety signs.

This International Standard will be maintained electronically through the use of a database. The indexes of this database will be used in these summaries as search engines with each registered safety sign having a unique reference number¹⁾.

1) The registered safety signs can be found at <http://cdb.iso.org>.

4.2 Referent (safety meaning)

Table 1 gives the list of referents in alphabetical order and provides the safety sign functional reference number.

Table 1 — Summary of referents in alphabetical order

Referent (safety meaning)	Functional reference number
Automated external heart defibrillator	E010
Automatic start-up, warning	W018
Battery charging, warning	W026
Biological hazard, warning	W009
Break to obtain access	E008
Connect an earth terminal to the ground	M005
Corrosive substance, warning	W023
Counterrotating rollers, warning	W025
Crushing, warning	W019
Crushing of hands, warning	W024
Disconnect before carrying out maintenance or repair	M021
Disconnect mains plug from electrical outlet	M006
Doctor	E009
Do not alter the state of the switch	P031
Do not extinguish with water	P011
Do not obstruct	P023
Do not tie knots in rope	P030
Do not touch	P010
Do not use for face grinding	P032
Do not use for wet grinding	P033
Do not use lift in the event of fire	P020
Do not use this device in a bathtub, shower or water-filled reservoir	P026
Do not use this incomplete scaffold	P025
Do not use this lift for people	P027
Do not use with hand-held grinding machine	P034
Do not walk or stand here	P024
Do not wear gloves	P028
Drop (fall), warning	W008
Electricity, warning	W012
Emergency exit (left hand)	E001
Emergency exit (right hand)	E002
Emergency telephone	E004
Emergency window with escape ladder	E016

Table 1 (continued)

Referent (safety meaning)	Functional reference number
Evacuation assembly point	E007
Explosive material, warning	W002
Eyewash station	E011
Fire alarm call point	F005
Fire emergency telephone	F006
Fire extinguisher	F001
Firefighting equipment, collection of	F004
Fire hose reel	F002
Fire ladder	F003
First aid	E003
Flammable material, warning	W021
Floor-level obstacle, warning	W007
Forklift trucks and other industrial vehicles, warning	W014
General mandatory action sign	M001
General prohibition sign	P001
General warning sign	W001
Guard dog, warning	W013
Hot surface, warning	W017
Laser beam, warning	W004
Low temperature/freezing conditions, warning	W010
Magnetic field, warning	W006
No access for forklift trucks and other industrial vehicles	P006
No access for people with active implanted cardiac devices	P007
No access for people with metallic implants	P014
No activated mobile phones	P013
No dogs	P021
No eating or drinking	P022
No heavy load	P012
No metallic articles or watches	P008
No open flame; Fire, open ignition source and smoking prohibited	P003
No photography	P029
No pushing	P017
No reaching in	P015
No sitting	P018
No smoking	P002
No stepping on surface	P019
No thoroughfare	P004

Table 1 (continued)

Referent (safety meaning)	Functional reference number
Non-ionizing radiation, warning	W005
Not drinking water	P005
Opaque eye protection must be worn	M007
Optical radiation, warning	W027
Overhead load, warning	W015
Overhead obstacle, warning	W020
Oxidizing substance, warning	W028
Pressurized cylinder, warning	W029
Protect infants' eyes with opaque eye protection	M025
Radioactive material or ionizing radiation, warning	W003
Refer to instruction manual/booklet	M002
Rescue window	E017
Safety shower	E012
Sharp element, warning	W022
Slippery surface, warning	W011
Stretcher	E013
Toxic material, warning	W016
Turn anticlockwise to open	E018
Turn clockwise to open	E019
Use barrier cream	M022
Use footbridge	M023
Use handrail	M012
Use protective apron	M026
Use this walkway	M024
Wash your hands	M011
Wear ear protection	M003
Wear eye protection	M004
Wear a face shield	M013
Wear head protection	M014
Wear high-visibility clothing	M015
Wear a mask	M016
Wear protective clothing	M010
Wear protective gloves	M009
Wear respiratory protection	M017
Wear safety belts	M020
Wear safety footwear	M008
Wear a safety harness	M018
Wear a welding mask	M019

4.3 Categorization of safety signs

Safety signs are categorized according to their function as follows:

- E is the category for signs indicating an evacuation route, the location of safety equipment or a safety facility, or a safety action (safe condition signs);
- F is the category for fire equipment signs;
- M is the category for mandatory action signs;
- P is the category for prohibition signs;
- W is the category for warning signs.

Table 2 summarizes the registered safety signs in terms of safety sign category in accordance with ISO 3864-1.

5 Registered safety signs

Tables 3 to 7 give safety sign originals in a uniform 70 mm size with corner marks to enable accurate enlargement and reduction scaling. The sign illustrations are shown without borders in order to allow for consistent reproduction scaling, though a border can be useful to achieve a luminance contrast between the safety sign and its background when mounted or displayed. The safety signs should be reproduced exactly as shown in Tables 3 to 7. However some degree of graphical modification is permitted when cultural differences or special application formats need to be considered, provided the original meaning is retained and comprehension of the safety sign is maintained. Consistent reproduction and use of these safety signs will lead to a progressively improved degree of comprehension at the international level.

In cases where the orientation of the graphical symbol is not essential to the meaning of the safety sign, the graphical symbol may be reproduced in a mirrored form. For prohibition signs, it is essential that the prohibition bar does not obscure significant details of the graphical symbol.

NOTE The graphical symbol is the complete image containing all the graphical symbol elements as shown in the registered safety sign.

Where a registered safety sign is not available to indicate a particular desired meaning, the meaning shall be obtained either by developing a new safety sign following the design principles of ISO 3864-1 and ISO 3864-3 or by using the appropriate general sign (ISO 7010-M001, -P001, -W001), together with supplementary safety information.

Tables 3 to 7 present the safety sign originals according to their category as follows:

- | | | |
|-----|--|-------------|
| — E | Signs indicating an evacuation route, the location of safety equipment or a safety facility, or a safety action (safe condition signs) | see Table 3 |
| — F | Fire equipment signs | see Table 4 |
| — M | Mandatory action signs | see Table 5 |
| — P | Prohibition signs | see Table 6 |
| — W | Warning signs | see Table 7 |

Tables 3 to 7 also give a description of the application of each safety sign.

Table 2 — Summary of all safety signs

Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign					
Reference number Referent	E001 Emergency exit (left hand)	F001 Fire extinguisher	M001 General mandatory action sign	P001 General prohibition sign	W001 General warning sign
Safety sign					
Reference number Referent	E002 Emergency exit (right hand)	F002 Fire hose reel	M002 Refer to instruction manual/booklet	P002 No smoking	W002 Warning; Explosive material
Safety sign					
Reference number Referent	E003 First aid	F003 Fire ladder	M003 Wear ear protection	P003 No open flame; Fire, open ignition source and smoking prohibited	W003 Warning; Radioactive material or ionizing radiation
Safety sign					
Reference number Referent	E004 Emergency telephone	F004 Collection of firefighting equipment	M004 Wear eye protection	P004 No thoroughfare	W004 Warning; Laser beam
Safety sign	withdrawn				
Reference number Referent	E005 Direction, arrow (90° increments), safe condition	F005 Fire alarm call point	M005 Connect an earth terminal to the ground	P005 Not drinking water	W005 Warning; Non-ionizing radiation

Table 2 (continued)




















Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign	withdrawn				
Reference number	E006	F006	M006	P006	W006
Referent	Direction, 45° arrow (90° increments), safe condition	Fire emergency telephone	Disconnect mains plug from electrical outlet	No access for forklift trucks and other industrial vehicles	Warning; Magnetic field
Safety sign		—			
Reference number	E007	—	M007	P007	W007
Referent	Evacuation assembly point	—	Opaque eye protection must be worn	No access for people with active implanted cardiac devices	Warning; Floor-level obstacle
Safety sign		—			
Reference number	E008	—	M008	P008	W008
Referent	Break to obtain access	—	Wear safety footwear	No metallic articles or watches	Warning; Drop (fall)
Safety sign		—		in the process	
Reference number	E009	—	M009	—	W009
Referent	Doctor	—	Wear protective gloves	—	Warning; Biological hazard
Safety sign		—			
Reference number	E010	—	M010	P010	W010
Referent	Automated external heart defibrillator	—	Wear protective clothing	Do not touch	Warning; Low temperature/ freezing conditions

Table 2 (continued)



















Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign		—			
Reference number	E011	—	M011	P011	W011
Referent	Eyewash station	—	Wash your hands	Do not extinguish with water	Warning; Slippery surface
Safety sign		—			
Reference number	E012	—	M012	P012	W012
Referent	Safety shower	—	Use handrail	No heavy load	Warning; Electricity
Safety sign		—			
Reference number	E013	—	M013	P013	W013
Referent	Stretcher	—	Wear a face shield	No activated mobile phones	Warning; Guard dog
Safety sign	in the process	—			
Reference number	—	—	M014	P014	W014
Referent	—	—	Wear head protection	No access for people with metallic implants	Warning; Forklift trucks and other industrial vehicles
Safety sign	in the process	—			
Reference number	—	—	M015	P015	W015
Referent	—	—	Wear high-visibility clothing	No reaching in	Warning; Overhead load

Table 2 (continued)



















Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign		—		in the process	
Reference number	E016	—	M016	—	W016
Referent	Emergency window with escape ladder	—	Wear a mask	—	Warning; Toxic material
Safety sign		—			
Reference number	E017	—	M017	P017	W017
Referent	Rescue window	—	Wear respiratory protection	No pushing	Warning; Hot surface
Safety sign		—			
Reference number	E018	—	M018	P018	W018
Referent	Turn anticlockwise to open	—	Wear a safety harness	No sitting	Warning; Automatic start-up
Safety sign		—			
Reference number	E019	—	M019	P019	W019
Referent	Turn clockwise to open	—	Wear a welding mask	No stepping on surface	Warning; Crushing
Safety sign	—	—			
Reference number	—	—	M020	P020	W020
Referent	—	—	Wear safety belts	Do not use lift in the event of fire	Warning; Overhead obstacle

Table 2 (continued)
















Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign	—	—			
Reference number	—	—	M021	P021	W021
Referent	—	—	Disconnect before carrying out main- tenance or repair	No dogs	Warning; Flammable material
Safety sign	—	—			
Reference number	—	—	M022	P022	W022
Referent	—	—	Use barrier cream	No eating or drinking	Warning; Sharp element
Safety sign	—	—			
Reference number	—	—	M023	P023	W023
Referent	—	—	Use footbridge	Do not obstruct	Warning; Corrosive substance
Safety sign	—	—			
Reference number	—	—	M024	P024	W024
Referent	—	—	Use this walkway	Do not walk or stand here	Warning; Crushing of hands
Safety sign	—	—			
Reference number	—	—	M025	P025	W025
Referent	—	—	Protect infants' eyes with opaque eye protection	Do not use this incomplete scaffold	Warning; Counterrotating rollers

Table 2 (continued)











Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign	—	—			
Reference number	—	—	M026	P026	W026
Referent	—	—	Use protective apron	Do not use this device in a bathtub, shower, or water-filled reservoir	Warning; Battery charging
Safety sign	—	—	—		
Reference number	—	—	—	P027	W027
Referent	—	—	—	Do not use this lift for people	Warning; Optical radiation
Safety sign	—	—	—		
Reference number	—	—	—	P028	W028
Referent	—	—	—	Do not wear gloves	Warning; Oxidizing substance
Safety sign	—	—	—		
Reference number	—	—	—	P029	W029
Referent	—	—	—	No photography	Warning; pressurized cylinder
Safety sign	—	—	—		—
Reference number	—	—	—	P030	—
Referent	—	—	—	Do not tie knots in rope	—

Table 2 (continued)





Safety sign, reference number and referent	Category				
	E	F	M	P	W
	Evacuation route, location of safety equipment or safety facility, safety action (safe condition signs)	Fire equipment signs	Mandatory action signs	Prohibition signs	Warning signs
Safety sign	—	—	—		—
Reference number	—	—	—	P031	—
Referent	—	—	—	Do not alter the state of the switch	—
Safety sign	—	—	—		—
Reference number	—	—	—	P032	—
Referent	—	—	—	Do not use for face grinding	—
Safety sign	—	—	—		—
Reference number	—	—	—	P033	—
Referent	—	—	—	Do not use for wet grinding	—
Safety sign	—	—	—		—
Reference number	—	—	—	P034	—
Referent	—	—	—	Do not use with hand-held grinding machine	—

Table 3 — Description and application of referent for signs indicating an evacuation route, the location of safety equipment or a safety facility, or a safety action (safe condition signs) (category E)

	<p>Reference No.</p> <p style="text-align: center;">ISO 7010-E001</p>
	<p>Referent</p> <p style="text-align: center;">Emergency exit (left hand)</p>
	<p>Function</p> <p>To indicate an escape route to a place of safety</p>
	<p>Image content</p> <p>Human figure moving (to the left) through doorway</p>
<p>Hazard</p> <p>Not being able to locate an escape route to a place of safety which is provided for evacuation in the event of an emergency</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Being aware of the location of an escape route to a place of safety in the event of an emergency</p> <p>Related referents</p> <p>ISO 7010-E002, ISO 7010-E016, ISO 7010-E017</p> <p>Additional information</p> <p>Test data obtained according to ISO 9186-1:2007 are not available. However, this safety sign has been the subject of extensive research in Japan and the design selected has received the best comprehension results. A supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p> <p>Supplementary arrow sign (type D of ISO 3864-3) in white on green to be used to give directional information (direction examples, the arrows may be rotated in increments of 45°):</p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  </div> <div style="text-align: center;">  </div> </div>	

Table 3 (continued)

	Reference No. ISO 7010-E002
	Referent Emergency exit (right hand)
	Function To indicate an escape route to a place of safety
	Image content Human figure moving (to the right) through doorway
Hazard Not being able to locate an escape route to a place of safety which is provided for evacuation in the event of an emergency	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of an escape route to a place of safety in the event of an emergency	
Related referents ISO 7010-E001, ISO 7010-E016, ISO 7010-E017	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. However, this safety sign has been the subject of extensive research in Japan and the design selected has received the best comprehension results. A supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training. Supplementary arrow sign (type D of ISO 3864-3) in white on green to be used to give directional information (direction examples, the arrows may be rotated in increments of 45°):	
	

Table 3 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-E003</p>
	Referent <p style="text-align: center;">First aid</p>
	Function To indicate the location of first aid equipment or facilities or staff
	Image content First aid cross
Hazard Not being able to locate first aid equipment or facilities or staff in the event of injury or emergency Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of first aid equipment or facilities or staff Related referents ISO 7010-E004, ISO 7010-E009, ISO 7010-E010, ISO 7010-E011, ISO 7010-E012, ISO 7010-E013 Additional information This safety sign should be used for first aid equipment or facilities or staff for which/whom there is no registered safety sign. The first aid cross may be replaced with another element appropriate to cultural requirements. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-E004</p>
	Referent <p style="text-align: center;">Emergency telephone</p>
	Function To indicate the location of an emergency telephone
	Image content Telephone receiver (profile), first aid cross
Hazard Not being able to locate a telephone which is provided for use in the event of an emergency	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of an emergency telephone	
Related referents ISO 7010-E003, ISO 7010-E009, ISO 7010-E010, ISO 7010-E011, ISO 7010-E012, ISO 7010-E013, ISO 7010-F006	
Additional information The first aid cross may be replaced with another element appropriate to cultural requirements. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)

withdrawn	Reference No. <p style="text-align: center;">ISO 7010-E005</p>
	Referent <p style="text-align: center;">Direction, arrow (90° increments), safe condition</p>
	Function
	Image content
<p>Hazard</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Related referents</p> <p>Additional information This sign has been withdrawn as a registered safety sign, since it is to be used as a supplementary sign only.</p>	

Table 3 (continued)

withdrawn	Reference No. ISO 7010-E006
	Referent Direction, 45° arrow (90° increments), safe condition
	Function
	Image content
<p>Hazard</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Related referents</p> <p>Additional information This sign has been withdrawn as a registered safety sign, since it is to be used as a supplementary sign only.</p>	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E007</p>
	Referent <p style="text-align: center;">Evacuation assembly point</p>
	Function To indicate the location of a safe assembly point following evacuation
	Image content Two human figures and a head of a third figure in a group, four arrows coming from the corners pointing to them
Hazard Not being able to locate a safe assembly point following evacuation	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the evacuation assembly point which is provided to enable people to be accounted for following the evacuation of a building or premises	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E008</p>
	Referent <p style="text-align: center;">Break to obtain access</p>
	Function To indicate a cover which requires breaking to obtain access to an emergency exit device
	Image content Human fist and lower arm (outlined) holding a bar, uneven star shape
Hazard Not being able to open an emergency exit device	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Breaking the cover to gain access to the device that operates an emergency exit in the event of an emergency	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E009</p>
	Referent <p style="text-align: center;">Doctor</p>
	Function To indicate the location of a doctor for emergencies
	Image content Upper human figure with stethoscope, first aid cross
Hazard Not being able to locate an emergency doctor Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of an emergency doctor Related referents ISO 7010-E003, ISO 7010-E004, ISO 7010-E010, ISO 7010-E011, ISO 7010-E012, ISO 7010-E013 Additional information The first aid cross may be replaced with another element appropriate to cultural requirements. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E010</p>
	Referent <p style="text-align: center;">Automated external heart defibrillator</p>
	Function To indicate the location of an automated external heart defibrillator
	Image content Heart with lightning bolt in the middle, first aid cross
Hazard Not being able to locate an automated external heart defibrillator	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of an automated external heart defibrillator	
Related referents ISO 7010-E003, ISO 7010-E004, ISO 7010-E009, ISO 7010-E011, ISO 7010-E012, ISO 7010-E013	
Additional information The first aid cross may be replaced with another element appropriate to cultural requirements of the target group. Test data obtained according to ISO 9186-1:2007 are available from more than one country. Findings from testing showed that the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E011</p>
	Referent <p style="text-align: center;">Eyewash station</p>
	Function To indicate the location of an eyewash station
	Image content Eye above running water coming out of a shower head, first aid cross
Hazard Not being able to locate an eyewash station Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of an eyewash station Related referents ISO 7010-E003, ISO 7010-E004, ISO 7010-E009, ISO 7010-E010, ISO 7010-E012, ISO 7010-E013 Additional information The first aid cross may be replaced with another element appropriate to cultural requirements of the target group. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E012</p>
	Referent <p style="text-align: center;">Safety shower</p>
	Function To indicate the location of a safety shower
	Image content Human figure under running water coming out of a shower head, first aid cross
Hazard Not being able to locate a safety shower	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a safety shower	
Related referents ISO 7010-E003, ISO 7010-E004, ISO 7010-E009, ISO 7010-E010, ISO 7010-E011, ISO 7010-E013	
Additional information The first aid cross may be replaced with another element appropriate to cultural requirements of the target group. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E013</p>
	Referent <p style="text-align: center;">Stretcher</p>
	Function To indicate the location of a stretcher
	Image content Human figure on a stretcher, first aid cross
Hazard Not being able to locate a stretcher Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a stretcher Related referents ISO 7010-E003, ISO 7010-E004, ISO 7010-E009, ISO 7010-E010, ISO 7010-E011, ISO 7010-E012 Additional information The first aid cross may be replaced with another element appropriate to cultural requirements of the target group. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-E016</p>
	Referent <p style="text-align: center;">Emergency window with escape ladder</p>
	Function To indicate the location of an emergency window for escape with a permanently fixed escape ladder
	Image content Human figure, window and a ladder on the left
Hazard Not being able to locate an emergency window for escape in the event of an emergency	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of an emergency window in the event of an emergency	
Related referents ISO 7010-E001, ISO 7010-E002, ISO 7010-E017	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E017</p>
	Referent <p style="text-align: center;">Rescue window</p>
	Function To indicate the location of a rescue window where people can be rescued by a ladder by intervention forces
	Image content Human figure, window, firefighting vehicle with ladder
Hazard Not being able to locate a rescue window to be rescued by intervention forces in the event of an emergency evacuation Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a rescue window Related referents ISO 7010-E001, ISO 7010-E002, ISO 7010-E016 Additional information This safety sign has to be placed inside the building. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E018</p>
	Referent <p style="text-align: center;">Turn anticlockwise to open</p>
	Function <p>To signify that the doorknob of a security door on an escape route must be turned in an anticlockwise direction in order for the opening device to operate</p>
	Image content <p>Doorknob with semicircular anticlockwise arrow</p>
Hazard <p>Being unable to open a door on an escape route which has a security lock and an emergency opening device, in the event of an emergency</p>	
Human behaviour that is intended to be caused after understanding the safety sign's meaning <p>Turning the doorknob in an anticlockwise direction in order to open a door on an escape route which has a security lock, in the event of an emergency</p>	
Related referents <p>ISO 7010-E019</p>	
Additional information <p>This safety sign is intended to be used only on doors with a security locking mechanism.</p> <p>Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Table 3 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-E019</p>
	Referent <p style="text-align: center;">Turn clockwise to open</p>
	Function To signify that the doorknob of a security door on an escape route must be turned in a clockwise direction in order for the opening device to operate
	Image content Doorknob with semicircular clockwise arrow
Hazard Being unable to open a door on an escape route which has a security lock and an emergency opening device, in the event of an emergency Human behaviour that is intended to be caused after understanding the safety sign's meaning Turning the doorknob in a clockwise direction in order to open a door on an escape route which has a security lock, in the event of an emergency Related referents ISO 7010-E018 Additional information This safety sign is intended to be used only on doors with a security locking mechanism. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 4 — Description and application of referent for fire equipment signs (category F)


	Reference No. ISO 7010-F001
	Referent Fire extinguisher
	Function To indicate the location of a fire extinguisher
	Image content Fire extinguisher (profile) with label, flame determinant
Hazard Not being able to locate a fire extinguisher Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a fire extinguisher Related referents ISO 7010-F002, ISO 7010-F003, ISO 7010-F004, ISO 7010-F005, ISO 7010-F006 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 4 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-F002</p>
	Referent <p style="text-align: center;">Fire hose reel</p>
	Function To indicate the location of a fire hose reel
	Image content Seven vertical lines, one with a trapezoid underneath, circle with cross and line attached to vertical bar, flame determinant
Hazard Not being able to locate a fire hose reel Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a fire hose reel Related referents ISO 7010-F001, ISO 7010-F003, ISO 7010-F004, ISO 7010-F005, ISO 7010-F006 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 4 (continued)


	Reference No. ISO 7010-F003
	Referent Fire ladder
	Function To indicate the location of a ladder that is to be used exclusively for firefighting
	Image content Two converging vertical lines, six horizontal lines joining the vertical lines, flame determinant
Hazard Not being able to locate a fire ladder	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a fire ladder and recognizing that the use of this ladder is dedicated to firefighting only	
Related referents ISO 7010-F001, ISO 7010-F002, ISO 7010-F004, ISO 7010-F005, ISO 7010-F006	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 4 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-F004</p>
	Referent <p style="text-align: center;">Collection of firefighting equipment</p>
	Function To indicate the location of firefighting equipment
	Image content Fire helmet (profile), flame determinant
Hazard Not being able to locate firefighting equipment Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of firefighting equipment Related referents ISO 7010-F001, ISO 7010-F002, ISO 7010-F003, ISO 7010-F005, ISO 7010-F006 Additional information This safety sign should be used for firefighting equipment for which there is no registered safety sign. The fire helmet may be replaced with another fire helmet appropriate to cultural requirements. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 4 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-F005</p>
	Referent <p style="text-align: center;">Fire alarm call point</p>
	Function To indicate the location of a fire alarm call point
	Image content Hand (plan view) with one finger extended, dot in square (outlined) broken at bottom, flame determinant
Hazard Not being able to locate a fire alarm call point	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a fire alarm call point	
Related referents ISO 7010-F001, ISO 7010-F002, ISO 7010-F003, ISO 7010-F004, ISO 7010-F006	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 4 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-F006</p>
	Referent <p style="text-align: center;">Fire emergency telephone</p>
	Function To indicate the location of a fire emergency telephone
	Image content Telephone receiver (profile), flame determinant
Hazard Not being able to locate a fire emergency telephone Human behaviour that is intended to be caused after understanding the safety sign's meaning Being aware of the location of a fire emergency telephone Related referents ISO 7010-E004, ISO 7010-F001, ISO 7010-F002, ISO 7010-F003, ISO 7010-F004, ISO 7010-F005 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 — Description and application of referent for mandatory action signs (category M)

	Reference No. <p style="text-align: center;">ISO 7010-M001</p>
	Referent <p style="text-align: center;">General mandatory action sign</p>
	Function To signify a mandatory action
	Image content Exclamation mark
Hazard Risk to people not following the mandatory action specified by the supplementary sign Human behaviour that is intended to be caused after understanding the safety sign's meaning Carrying out the mandatory action specified by the supplementary sign Related referents ISO 7010-P001, ISO 7010-W001 Additional information This safety sign cannot be used on its own and requires a supplementary sign to give further information about the action to be taken.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M002</p>
	Referent <p style="text-align: center;">Refer to instruction manual/booklet</p>
	Function To signify that the instruction manual/booklet must be read
	Image content Upper human figure (right-hand profile) holding an open manual/booklet
Hazard Not reading the instruction manual/booklet before starting work or before operating equipment or machinery Human behaviour that is intended to be caused after understanding the safety sign's meaning Reading the instruction manual/booklet before starting work or before operating equipment or machinery Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M003</p>
	Referent <p style="text-align: center;">Wear ear protection</p>
	Function To signify that ear protection must be worn
	Image content Human head (front view) wearing ear protection
Hazard Noise Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing ear protection Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M004</p>
	Referent <p style="text-align: center;">Wear eye protection</p>
	Function To signify that eye protection must be used
	Image content Human head (front view) wearing eye protection
Hazard Flying objects/particles Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing eye protection Related referents ISO 7010-M007, ISO 7010-M013 Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M005</p>
	Referent <p style="text-align: center;">Connect an earth terminal to the ground</p>
	Function To signify that an earth terminal must be connected
	Image content Vertical line joining horizontal line with two progressively shorter parallel horizontal lines underneath
Hazard Electric shock, explosion, fire	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Connecting an earth terminal of a product to the ground	
Related referents ISO 7010-W012	
Additional information This safety sign relates to products employing a class I insulating system which requires protective earthing. Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	<p>Reference No.</p> <p style="text-align: center;">ISO 7010-M006</p>
	<p>Referent</p> <p style="text-align: center;">Disconnect mains plug from electrical outlet</p>
	<p>Function</p> <p>To signify that the mains plug must be disconnected from electrical outlet for the purposes of maintenance of electrical equipment, in the case of malfunction or when left unattended</p>
	<p>Image content</p> <p>Two fingers and thumb (outlined) holding a two-pin electrical plug, arrow pointing right, vertical line</p>
<p>Hazard</p> <p>Electric shock, fire</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Disconnecting the mains plug for the purposes of maintenance, in the case of malfunction or when left unattended</p> <p>Related referents</p> <p>ISO 7010-M021, ISO 7010-W012</p> <p>Additional information</p> <p>Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M007</p>
	Referent <p style="text-align: center;">Opaque eye protection must be worn</p>
	Function To signify that opaque eye protection must be worn
	Image content Human head (front view) wearing opaque eye protection
Hazard Visible or invisible rays Human behaviour that is intended to be caused after understanding the safety sign's meaning Ensuring that the people undergoing treatment by visible or invisible rays are wearing opaque eye protection Related referents ISO 7010-M004, ISO 7010-M025 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M008</p>
	Referent <p style="text-align: center;">Wear safety footwear</p>
	Function To signify that safety footwear must be worn
	Image content Two safety boots, one shown in front, the other shown behind (outlined)
Hazard Feet striking or being struck by objects or being in contact with thermal or chemical materials	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing safety footwear	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)


	Reference No. ISO 7010-M009
	Referent Wear protective gloves
	Function To signify that protective gloves must be worn
	Image content Two protective gloves, one shown in front, the other shown behind (outlined)
Hazard Hands striking or being struck by objects or being in contact with thermal or chemical materials	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing protective gloves	
Related referents ISO 7010-M022	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M010</p>
	Referent <p style="text-align: center;">Wear protective clothing</p>
	Function To signify that protective clothing must be worn
	Image content Overall (front view)
Hazard Chemicals, heat or cold Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing protective clothing Related referents ISO 7010-M026 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M011</p>
	Referent <p style="text-align: center;">Wash your hands</p>
	Function To signify that hands must be washed
	Image content Two hands, one shown in front, the other shown behind (outlined), three lines of four dots, tap
Hazard Infection or contamination	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Washing hands before starting work task and after finishing work task	
Related referents ISO 7010-M022	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M012</p>
	Referent <p style="text-align: center;">Use handrail</p>
	Function To signify that the handrail must be used
	Image content Upper human figure with left arm touching diagonal line
Hazard Falling, slipping or tripping Human behaviour that is intended to be caused after understanding the safety sign's meaning Holding the handrail when using stairs, escalators or moving walkways Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. ISO 7010-M013
	Referent Wear a face shield
	Function To signify that a face shield must be worn
	Image content Human head (left-hand profile) wearing a face shield
Hazard Flying objects/particles Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing a face shield Related referents ISO 7010-M004, ISO 7010-M016, ISO 7010-M019 Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M014</p>
	Referent <p style="text-align: center;">Wear head protection</p>
	Function To signify that head protection must be worn
	Image content Human head (left-hand profile) wearing head protection
Hazard Objects falling on head or head striking objects Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing head protection Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M015</p>
	Referent <p style="text-align: center;">Wear high-visibility clothing</p>
	Function To signify that high-visibility clothing must be worn
	Image content Sleeveless jacket (front view) with two vertical and two horizontal lines
Hazard Moving vehicles or equipment	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing high-visibility clothing	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M016</p>
	Referent <p style="text-align: center;">Wear a mask</p>
	Function To signify that a face mask must be worn
	Image content Human head (left-hand profile) wearing a mask
Hazard Particulates in the air Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing a face mask Related referents ISO 7010-M013, ISO 7010-M017 Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M017</p>
	Referent <p style="text-align: center;">Wear respiratory protection</p>
	Function To signify that respiratory protection must be worn
	Image content Human head (front view) wearing respiratory protection
Hazard Harmful substances (e.g. noxious gases)	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing respiratory protection	
Related referents ISO 7010-M016	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M018</p>
	Referent <p style="text-align: center;">Wear a safety harness</p>
	Function To signify that a safety harness must be worn
	Image content Human figure wearing a safety harness
Hazard Falling from a height Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing a safety harness Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M019</p>
	Referent <p style="text-align: center;">Wear a welding mask</p>
	Function To signify that a welding mask must be worn
	Image content Human head (left-hand profile) wearing a welding mask
Hazard Hot flying particles, intense light and UV radiation from welding activity	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing a welding mask	
Related referents ISO 7010-M013	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M020</p>
	Referent <p style="text-align: center;">Wear safety belts</p>
	Function To signify that safety belts must be used
	Image content End of belts with a buckle and two arrows pointing to each other
Hazard Being projected from the seat of a vehicle or equipment Human behaviour that is intended to be caused after understanding the safety sign's meaning Wearing safety belts Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M021</p>
	Referent <p style="text-align: center;">Disconnect before carrying out maintenance or repair</p>
	Function <p>To signify that the machine or the equipment, which is not connected to mains by a plug, has to be disconnected from all sources of power before carrying out maintenance or repair</p>
	Image content <p>Horizontal arrow pointing to the right; one vertical short thick line attached to a circle at the bottom with a longer thick line at an angle to the right attached to the top of the circle; a further thick line in the same plane as the lower one, separated from the line at an angle</p>
Hazard Machine or equipment running during maintenance or repair	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Disconnecting the machine or equipment before carrying out maintenance or repair	
Related referents ISO 7010-M006, ISO 7010-P031	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M022</p>
	Referent <p style="text-align: center;">Use barrier cream</p>
	Function To signify that the skin has to be protected with an appropriate barrier cream
	Image content Human hand, tube, wavy line
Hazard Damage to the skin Human behaviour that is intended to be caused after understanding the safety sign's meaning Protecting the skin with barrier cream before starting work or putting on gloves Related referents ISO 7010-M009 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M023</p>
	Referent <p style="text-align: center;">Use footbridge</p>
	Function To signify that a footbridge must be used
	Image content Human figure walking on a footbridge
Hazard Moving vehicles, obstructions, or tripping or falling	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Using the footbridge to avoid dangerous areas	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-M024</p>
	Referent <p style="text-align: center;">Use this walkway</p>
	Function To signify that pedestrians must use a designated walkway
	Image content Human figure walking (left hand)
Hazard Areas unsafe for pedestrians Human behaviour that is intended to be caused after understanding the safety sign's meaning Pedestrians using the designated walkway Related referents ISO 7010-P004 Additional information Test data obtained according to ISO 9186-1:2007 are available from more than one country. Findings from testing showed that the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)


	Reference No. ISO 7010-M025
	Referent Protect infants' eyes with opaque eye protection
	Function To signify that opaque eye protection must be worn by infants
	Image content Infant wearing opaque eye protection
Hazard Intense light incident on infant's eyes Human behaviour that is intended to be caused after understanding the safety sign's meaning Ensuring that the infant's eyes are protected before switching the equipment on or before placing the infant into the radiated area Related referents ISO 7010-M007 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 5 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-M026</p>
	Referent <p style="text-align: center;">Use protective apron</p>
	Function To signify that the front of the body must be protected by an apron
	Image content Human figure with an apron
Hazard Front of body striking or being struck by objects or coming into contact with substances or materials Human behaviour that is intended to be caused after understanding the safety sign's meaning Protecting the front of the body Related referents ISO 7010-M010 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 — Description and application of referent for prohibition signs (category P)

	Reference No. <p style="text-align: center;">ISO 7010-P001</p>
	Referent <p style="text-align: center;">General prohibition sign</p>
	Function To signify a prohibited action
	Image content None
Hazard Risk to people specified by the supplementary sign Human behaviour that is intended to be caused after understanding the safety sign's meaning Not doing an action specified by the supplementary sign Related referents ISO 7010-M001, ISO 7010-W001 Additional information This safety sign cannot be used on its own and requires a supplementary sign to give further information about the action which is prohibited.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P002</p>
	Referent <p style="text-align: center;">No smoking</p>
	Function To prohibit smoking
	Image content Cigarette (profile, outlined) with two wavy lines
Hazard Fire or explosion caused by lit cigarettes or other smoking materials or harm from the smoke Human behaviour that is intended to be caused after understanding the safety sign's meaning Not smoking Related referents ISO 7010-P003 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P003</p>
	Referent <p style="text-align: center;">No open flame; Fire, open ignition source and smoking prohibited</p>
	Function To prohibit smoking and all forms of open flame
	Image content Match (profile, outlined), flame
Hazard Fire or explosion caused by an open flame, open ignition source or smoking	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Not having an open flame or open ignition source and not smoking	
Related referents ISO 7010-P002, ISO 7010-W021	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P004</p>
	Referent <p style="text-align: center;">No thoroughfare</p>
	Function To prohibit the use of a thoroughfare by pedestrians
	Image content Human figure walking (left hand)
Hazard Collision with vehicles or machinery Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using the thoroughfare Related referents ISO 7010-M024 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P005</p>
	Referent <p style="text-align: center;">Not drinking water</p>
	Function To prohibit drinking of unsuitable water
	Image content Tap above glass, two wavy lines
Hazard Water unsuitable for drinking Human behaviour that is intended to be caused after understanding the safety sign's meaning Not drinking the water Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P006</p>
	Referent <p style="text-align: center;">No access for forklift trucks and other industrial vehicles</p>
	Function To prohibit the use of forklift trucks and other industrial vehicles
	Image content Forklift truck (left-hand profile) with human figure
Hazard Moving forklift trucks and other industrial vehicles Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using forklift trucks and other industrial vehicles Related referents ISO 7010-W014 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P007</p>
	Referent <p style="text-align: center;">No access for people with active implanted cardiac devices</p>
	Function To prohibit people with active implanted cardiac devices from entering a designated area
	Image content Heart shape and representation of pulse generator connected by curved line
Hazard Interference to the operation of or damage to active implanted cardiac devices from equipment generating strong electromagnetic fields	
Human behaviour that is intended to be caused after understanding the safety sign's meaning People with active implanted cardiac devices not entering a designated area	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P008</p>
	Referent <p style="text-align: center;">No metallic articles or watches</p>
	Function To prohibit metallic articles or watches
	Image content Face and part of strap of an analogue wristwatch, flat side of a key
Hazard Strong magnetic fields Human behaviour that is intended to be caused after understanding the safety sign's meaning Removing or not wearing metallic articles or watches Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P010</p>
	Referent <p style="text-align: center;">Do not touch</p>
	Function To prohibit touching objects/parts of an object
	Image content Hand, horizontal line underneath
Hazard Dangerous surfaces Human behaviour that is intended to be caused after understanding the safety sign's meaning Not touching objects or parts of an object Related referents ISO 7010-P015 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P011</p>
	Referent <p style="text-align: center;">Do not extinguish with water</p>
	Function To prohibit using water to extinguish a fire
	Image content Bucket, area outlined by wavy line, flame
Hazard Dangerous reaction from the application of water to a burning substance Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using water to extinguish a fire Related referents ISO 7010-W021 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. ISO 7010-P012
	Referent No heavy load
	Function To prohibit the placing of heavy objects on a surface
	Image content Weight resting on the two parts of a line which is broken in the centre so that the two halves are separated and each inclines downward
Hazard Breakage due to heavy load	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Not placing any heavy objects on a surface	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training. In spite of this, the following needs to be considered: “Heavy” depends on the context of use and if it needs to be specified, a supplementary sign should be added stating the maximum permissible load, e.g. as follows: max. 100 kg.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P013</p>
	Referent <p style="text-align: center;">No activated mobile phone</p>
	Function To prohibit activated mobile phones
	Image content Mobile phone (front view), six curved lines
Hazard Electromagnetic field Human behaviour that is intended to be caused after understanding the safety sign's meaning Turning the mobile phone off or not switching it on Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P014</p>
	Referent <p style="text-align: center;">No access for people with metallic implants</p>
	Function To prohibit access of people with metallic implants
	Image content Hip joint and socket (outlined) joined by a black hip implant
Hazard Invisible rays causing a rise in temperature of a metallic implant	
Human behaviour that is intended to be caused after understanding the safety sign's meaning People with metallic implants not entering a designated area	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P015</p>
	Referent <p style="text-align: center;">No reaching in</p>
	Function To prohibit people putting hands into openings
	Image content Hand between two converging lines
Hazard Injury to hands Human behaviour that is intended to be caused after understanding the safety sign's meaning Not putting hands into designated openings Related referents ISO 7010-P010 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P017</p>
	Referent <p style="text-align: center;">No pushing</p>
	Function To prohibit pushing against an object
	Image content Horizontal line and vertical block with human figure pushing against it
Hazard Objects overbalancing and falling Human behaviour that is intended to be caused after understanding the safety sign's meaning Not pushing an object Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P018</p>
	Referent <p style="text-align: center;">No sitting</p>
	Function To prohibit sitting on a surface
	Image content Human figure in sitting position, horizontal line
Hazard Surface unsuitable to sit on Human behaviour that is intended to be caused after understanding the safety sign's meaning Not sitting on an unsuitable surface Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P019</p>
	Referent <p style="text-align: center;">No stepping on surface</p>
	Function To prohibit stepping onto a surface
	Image content Human figure stepping up, line with right angle
Hazard Surface unsuitable for stepping onto Human behaviour that is intended to be caused after understanding the safety sign's meaning Not stepping onto an unsuitable surface Related referents ISO 7010-P024 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P020</p>
	Referent <p style="text-align: center;">Do not use lift in the event of fire</p>
	Function To prohibit use of lift in the event of fire
	Image content Outline of lift with two human figures standing inside and flames at the right-hand side of the lift
Hazard Being trapped in a lift during a fire Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using lift in the event of fire Related referents ISO 7010-P027 Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P021</p>
	Referent <p style="text-align: center;">No dogs</p>
	Function To prohibit taking dogs into designated areas
	Image content Dog (right-hand profile)
Hazard Infections due to dogs; harming of people caused by dog bites	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Not taking dogs into a designated area	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P022</p>
	Referent <p style="text-align: center;">No eating or drinking</p>
	Function To prohibit eating and drinking
	Image content Three horizontal lines alongside a cup with straw
Hazard Ingestion of dangerous substances by food and drink contaminated at a designated area Human behaviour that is intended to be caused after understanding the safety sign's meaning Not eating or drinking in the designated area Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. ISO 7010-P023
	Referent Do not obstruct
	Function To prohibit the obstruction of a designated clear area
	Image content Crate, horizontal line underneath
Hazard Obstruction in a designated clear area	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Not placing an obstruction in a designated clear area (e.g. escape routes, emergency exits, passageways)	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P024</p>
	Referent <p style="text-align: center;">Do not walk or stand here</p>
	Function To prohibit walking or standing on a designated area
	Image content Two footprints
Hazard Areas which are unsafe for people to walk or stand on Human behaviour that is intended to be caused after understanding the safety sign's meaning Keeping off a designated area Related referents ISO 7010-P019 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. ISO 7010-P025
	Referent Do not use this incomplete scaffold
	Function To prohibit the use of scaffolding systems which are not complete
	Image content Human figure (right-hand profile) walking on a broken horizontal bar surrounded by vertical and horizontal lines
Hazard Incomplete scaffold Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using an incomplete scaffold Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are available from more than one country. Findings from testing showed that the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P026</p>
	Referent <p style="text-align: center;">Do not use this device in a bathtub, shower or water-filled reservoir</p>
	Function To prohibit the use of unsuitable electrical equipment in or near water
	Image content Shower and bathtub
Hazard Electric shock Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using electrically powered equipment in bathtubs, showers or water-filled reservoirs Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P027</p>
	Referent <p style="text-align: center;">Do not use this lift for people</p>
	Function To prohibit the use of the lift for the transportation of people
	Image content Human figure (front view) in a rectangle, short arrows above and underneath the rectangle
Hazard Goods or freight lifts without the safety features necessary for the transportation of people Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using the lift for the transportation of people Related referents ISO 7010-P020 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P028</p>
	Referent <p style="text-align: center;">Do not wear gloves</p>
	Function To prohibit the use of gloves when operating a machine with drawing-in hazard
	Image content Two gloves, one outlined, one filled
Hazard Drawing-in hazard to people wearing gloves while operating a machine Human behaviour that is intended to be caused after understanding the safety sign's meaning Operating a machine with drawing-in hazard without wearing gloves Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P029</p>
	Referent <p style="text-align: center;">No photography</p>
	Function To prohibit the taking of photographs
	Image content Camera
Hazard Distraction of drivers, operatives and people working, particularly in dark environments Human behaviour that is intended to be caused after understanding the safety sign's meaning Not taking photographs Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P030</p>
	Referent <p style="text-align: center;">Do not tie knots in rope</p>
	Function To prohibit tying knots in a climbing rope
	Image content Climbing rope with a knot
Hazard Knots in a climbing rope Human behaviour that is intended to be caused after understanding the safety sign's meaning Not tying any knots in a climbing rope Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. ISO 7010-P031
	Referent Do not alter the state of the switch
	Function To prohibit any change of the current energetic or mechanical state of a machine or equipment
	Image content Switch and two arrows
Hazard Change of the current energetic or mechanical state of a machine or equipment Human behaviour that is intended to be caused after understanding the safety sign's meaning Not switching Related referents ISO 7010-M021 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-P032</p>
	Referent <p style="text-align: center;">Do not use for face grinding</p>
	Function To prohibit the use of the grinding disc for face grinding
	Image content Horizontal line with two thicknesses and an angled step; grinding machine at an angle to the line
Hazard Breakage of grinding disc due to overstressing leading to flying objects Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using the grinding disc for face grinding Related referents ISO 7010-P033, ISO 7010-P034 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. ISO 7010-P033
	Referent Do not use for wet grinding
	Function To prohibit the use of the grinding disc for wet grinding
	Image content Horizontal line, two circles with random infilling of dots and outer circle touching line, tap with water drops
Hazard Breakage of grinding disc due to overstressing leading to flying objects Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using the grinding disc for wet grinding Related referents ISO 7010-P032, ISO 7010-P034 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 6 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-P034</p>
	Referent <p style="text-align: center;">Do not use with hand-held grinding machine</p>
	Function To prohibit the use of the grinding disc with a hand-held grinding machine
	Image content Hand holding a grinding machine
Hazard Breakage of grinding disc due to overstressing leading to flying objects Human behaviour that is intended to be caused after understanding the safety sign's meaning Not using the grinding disc with a hand-held grinding machine Related referents ISO 7010-P032, ISO 7010-P033 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 — Description and application of referent for warning signs (category W)


	Reference No. <p style="text-align: center;">ISO 7010-W001</p>
	Referent <p style="text-align: center;">General warning sign</p>
	Function To signify a general warning
	Image content Exclamation mark
Hazard Risk to people specified by the supplementary sign Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care regarding the hazard specified by the supplementary sign Related referents ISO 7010-M001, ISO 7010-P001 Additional information This safety sign cannot be used on its own and requires a supplementary sign to give further information about the hazard.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W002</p>
	Referent <p style="text-align: center;">Warning; Explosive material</p>
	Function To warn of explosive materials
	Image content Part of filled circle with radiating triangular lines and irregular shapes
Hazard Explosion Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when in the vicinity of or handling explosive materials Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W003</p>
	Referent <p style="text-align: center;">Warning; Radioactive material or ionizing radiation</p>
	Function To warn of radioactive materials or ionizing radiation
	Image content Circle with three circular sectors around it
Hazard Radioactivity and ionizing radiation	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid exposure to radioactive material or ionizing radiation	
Related referents ISO 7010-W005, ISO 7010-W027	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W004</p>
	Referent <p style="text-align: center;">Warning; Laser beam</p>
	Function To warn of a laser beam
	Image content Circle with 24 regular equally spaced radiating lines, 12 shorter of equal length, 11 longer of equal length and one longer reaching horizontally the right-hand side of the triangle
Hazard Laser beam	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid exposure to a laser beam	
Related referents ISO 7010-W027	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W005</p>
	Referent <p style="text-align: center;">Warning; Non-ionizing radiation</p>
	Function To warn of non-ionizing radiation
	Image content Circle with three arc-shaped lines of increasing length on each side symmetrically located, with a trapezoid underneath
Hazard Non-ionizing radiation	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid exposure to non-ionizing radiation	
Related referents ISO 7010-W003, ISO 7010-W027	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W006</p>
	Referent <p style="text-align: center;">Warning; Magnetic field</p>
	Function To warn of a magnetic field
	Image content Hoop with two outlined sections at bottom, two arc-shaped lines on each side of the outlined section
Hazard Strong magnetic field Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid exposure to a strong magnetic field Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W007</p>
	Referent <p style="text-align: center;">Warning; Floor-level obstacle</p>
	Function To warn of a floor-level obstacle
	Image content Human figure falling forwards, thick horizontal line by forward leg
Hazard Floor-level obstacle	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when in the vicinity of a floor-level obstacle	
Related referents ISO 7010-W008, ISO 7010-W011, ISO 7010-W020	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W008</p>
	Referent <p style="text-align: center;">Warning; Drop (fall)</p>
	Function To warn of a drop
	Image content Human figure falling backwards from the edge of a surface
Hazard Drop Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when in the vicinity of a drop Related referents ISO 7010-W007, ISO 7010-W011 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W009</p>
	Referent <p style="text-align: center;">Warning; Biological hazard</p>
	Function To warn of a biological hazard
	Image content Circle overlaid by three equal pincer-shaped circles
Hazard Virus or toxin	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid exposure to a biological hazard	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W010</p>
	Referent <p style="text-align: center;">Warning; Low temperature/ freezing conditions</p>
	Function To warn of low temperature or freezing conditions
	Image content Snowflake
Hazard Low temperature or freezing conditions Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid exposure to low temperature or freezing conditions Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W011</p>
	Referent <p style="text-align: center;">Warning; Slippery surface</p>
	Function To warn of a slippery surface
	Image content Human figure falling backwards, horizontal line underneath
Hazard Slippery surface Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid a slippery surface or being aware of it, taking care to avoid slipping Related referents ISO 7010-W007, ISO 7010-W008 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W012</p>
	Referent <p style="text-align: center;">Warning; Electricity</p>
	Function To warn of electricity
	Image content Lightning bolt
<p>Hazard Electricity</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid coming into contact with electricity</p> <p>Related referents ISO 7010-M005, ISO 7010-M006</p> <p>Additional information The graphical symbol is standardized and registered as IEC 60417-5036 "Dangerous voltage". Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W013</p>
	Referent <p style="text-align: center;">Warning; Guard dog</p>
	Function To warn of a guard dog
	Image content Head of a dog (left-hand profile) with collar
Hazard Guard dog	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Not entering an area patrolled by a guard dog without ensuring that the dog is under control	
Related referents ISO 7010-P021	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W014</p>
	Referent <p style="text-align: center;">Warning; Forklift trucks and other industrial vehicles</p>
	Function To warn of a forklift truck and other industrial vehicles
	Image content Forklift truck (left-hand profile) with human figure
Hazard Moving forklift trucks and other industrial vehicles Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid collision with moving forklift trucks and other industrial vehicles Related referents ISO 7010-P006 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W015</p>
	Referent <p style="text-align: center;">Warning; Overhead load</p>
	Function To warn of an overhead load
	Image content Box suspended at an angle from two ropes attached to a hook
Hazard Overhead load	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid being struck by or walking into an overhead load	
Related referents ISO 7010-W020	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W016</p>
	Referent <p style="text-align: center;">Warning; Toxic material</p>
	Function To warn of toxic material
	Image content Skull (outlined), behind it two crossed bones (outlined)
Hazard Poisoning Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid coming into contact with toxic material Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W017</p>
	Referent <p style="text-align: center;">Warning; Hot surface</p>
	Function To warn of a hot surface
	Image content Three parallel, vertical, s-shaped lines above a horizontal straight line
Hazard Hot surface	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid coming into contact with a hot surface	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W018</p>
	Referent <p style="text-align: center;">Warning; Automatic start-up</p>
	Function To warn of automatic activation
	Image content Circle with three connected curved lines
Hazard Automatically moving mechanical parts Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when in the vicinity of machinery with moving mechanical parts which may start automatically and thus unexpectedly Related referents — Additional information The graphical symbol is standardized and registered as ISO 7000-0017 "Automatic control (closed loop)". Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W019</p>
	Referent <p style="text-align: center;">Warning; Crushing</p>
	Function To warn of moving mechanical parts
	Image content Human figure between two hatched bars; an arrow from the right side pointing to the right bar and an arrow from the left side pointing to the left bar
Hazard Mechanical parts which can come together in a crushing movement	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid mechanisms with parts which can come together in a crushing movement	
Related referents ISO 7010-W024	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	<p>Reference No.</p> <p style="text-align: center;">ISO 7010-W020</p>
	<p>Referent</p> <p style="text-align: center;">Warning; Overhead obstacle</p>
	<p>Function</p> <p>To warn of an overhead obstacle</p>
	<p>Image content</p> <p>Upper human figure underneath an overhead obstacle and star to indicate contact</p>
<p>Hazard</p> <p>Overhead obstacle</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Taking care to avoid being struck by or walking into an overhead obstacle</p> <p>Related referents</p> <p>ISO 7010-W007, ISO 7010-W015</p> <p>Additional information</p> <p>Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W021</p>
	Referent <p style="text-align: center;">Warning; Flammable material</p>
	Function To warn of flammable material
	Image content Flame, horizontal line underneath
Hazard Fire Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid causing a fire by igniting flammable material Related referents ISO 7010-P003, ISO 7010-P011 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W022</p>
	Referent <p style="text-align: center;">Warning; Sharp element</p>
	Function To warn of a sharp element
	Image content Bandaged hand above a vertical line with a point
Hazard Sharp elements Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid injury from sharp elements (e.g. needles, blades) Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	Reference No. ISO 7010-W023
	Referent Warning; Corrosive substance
	Function To warn of a corrosive substance
	Image content Hand with indentation, two test tubes, four droplets, thick line with indentation
Hazard Corrosive substance	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when handling corrosive substances	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W024</p>
	Referent <p style="text-align: center;">Warning; Crushing of hands</p>
	Function To warn of a closing motion of mechanical parts of equipment
	Image content Hand between two horizontal lines, vertical arrow pointing downwards
Hazard Closing mechanical parts of equipment Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid injury to hands when in the vicinity of equipment with closing mechanical parts Related referents ISO 7010-W019 Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	Reference No. <p style="text-align: center;">ISO 7010-W025</p>
	Referent <p style="text-align: center;">Warning; Counterrotating rollers</p>
	Function To warn of counterrotating rollers
	Image content Small circle with internal curved arrow pointing in anti-clockwise direction, large circle with internal curved arrow pointing in clockwise direction
Hazard Drawing-in movement	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when in the vicinity of counterrotating rollers	
Related referents —	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Table 7 (continued)


	<p>Reference No.</p> <p style="text-align: center;">ISO 7010-W026</p>
	<p>Referent</p> <p style="text-align: center;">Warning; Battery charging</p>
	<p>Function</p> <p>To warn of batteries being charged</p>
	<p>Image content</p> <p>Box with cross and horizontal short line within; two filled squares directly located on the box above the cross and the horizontal short line; two curved lines above the filled square on the left side and irregular curved filled area at the right side of the box</p>
<p>Hazard</p> <p>Explosive atmosphere and acid</p> <p>Human behaviour that is intended to be caused after understanding the safety sign's meaning</p> <p>Ensuring adequate ventilation of the charging area and taking care to avoid coming into contact with acid</p> <p>Related referents</p> <p>—</p> <p>Additional information</p> <p>The graphical symbol is standardized and registered as ISO 7000-1152 “Battery open”.</p> <p>Test data obtained according to ISO 9186-1:2007 are available from more than one country. Findings from testing showed that the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.</p>	

Table 7 (continued)



	Reference No. <p style="text-align: center;">ISO 7010-W027</p>
	Referent <p style="text-align: center;">Warning; Optical radiation</p>
	Function To warn of optical radiation
	Image content Star with 11 points with circle in centre
Hazard Optical radiation (such as UV, visible radiation, IR)	
Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care to avoid injury to eyes and skin when in the vicinity of optical radiation	
Related referents ISO 7010-W003, ISO 7010-W004, ISO 7010-W005	
Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign did not reach the criteria of acceptability. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training. If necessary, a supplementary sign shall be used to give further information about the kind of optical radiation (e.g. UV, visible radiation, IR).	

Table 7 (continued)

	Reference No. <p style="text-align: center;">ISO 7010-W028</p>
	Referent <p style="text-align: center;">Warning; Oxidizing substance</p>
	Function To warn of an oxidizing substance
	Image content Flame, circle, horizontal line
Hazard Fire Human behaviour that is intended to be caused after understanding the safety sign's meaning Taking care when in the vicinity of oxidizing substances Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available from more than one country. Findings from national testing, however, showed that in one country the safety sign exceeded the criteria of acceptability. A supplementary text sign may be used to increase comprehension. If the safety sign is supplemented by manuals, instructions or training, a supplementary text sign may not be required.	

Table 7 (continued)

	Reference No. ISO 7010-W029
	Referent Warning; Pressurized cylinder
	Function To warn of a pressurized cylinder
	Image content Cylinder at angle with radiating triangular lines and irregular shapes, flame and horizontal line underneath
Hazard Exploding pressurized cylinder Human behaviour that is intended to be caused after understanding the safety sign's meaning Protecting pressurized cylinders from high temperatures or from being dropped or falling Related referents — Additional information Test data obtained according to ISO 9186-1:2007 are not available. Consequently, a supplementary text sign shall be used to increase comprehension except when the safety sign is supplemented by manuals, instructions or training.	

Bibliography

- [1] ISO 3864-2, *Graphical symbols — Safety colours and safety signs — Part 2: Design principles for product safety labels*
- [2] ISO 7000, *Graphical symbols for use on equipment — Index and synopsis*
- [3] ISO 9186-1:2007, *Graphical symbols — Test methods — Part 1: Methods for testing comprehensibility*
- [4] ISO 9186-2, *Graphical symbols — Test methods — Part 2: Method for testing perceptual quality*
- [5] ISO 16069, *Graphical symbols — Safety signs — Safety way guidance systems (SWGS)*
- [6] ISO 17398, *Safety colours and safety signs — Classification, performance and durability of safety signs*
- [7] ISO 20712-1, *Water safety signs and beach safety flags — Part 1: Specifications for water safety signs used in workplaces and public areas*
- [8] IEC 60417, *Graphical symbols for use on equipment*

